

UDC100 Digital Controller

Model Selection Guide

Instructions

- Select the desired key number. The arrow to the right marks the selection available.
- Make one selection each from Table I thru III using the column below the proper arrow.
- A dot (•) denotes unrestricted availability.

Key Number I II III IV V VI VII

DC1 _ _ - _ - _ - _ - _ - _ - _

KEY NUMBER	Description	Selection	Availability				
1/4 DIN Controller	Single loop controller single display	DC10N	↓				
	Single loop controller dual display	DC10D		↓			
	Single loop dual display + 1 alarm	DC11A			↓		
	Single loop dual display + timer	DC11T				↓	
	Dual loop dual display	DC12N					↓

TABLE I

Control Output Type	Electromechanical relay SPDT 10 amps	R	•	•	•	•	•
	SSR driver 12Vdc	S	•	•	•	•	•

TABLE II

Power Supply and Frequency	115/230 Vac	0 _	•	•	•	•	•
	24/48 Vac	1 _	•	•	•	•	•
	24/230 Vac	2 _	•	•	•	•	•
	50 Hz	_ 0	•	•	•	•	•
	60 Hz	_ 1	•	•	•	•	•

TABLE III

Input Type (Note 1)	T/C J : 0-300° C	JC1	•	•	•	•	•
	T/C J : 0-400° C	JC2	•	•	•	•	•
	T/C J : 0-537° C	JC3	•	•	•	•	•
	T/C J : 0-870° C	JC4	•	•	•	•	•
	T/C K : 0-537° C	KC1	•	•	•	•	•
	T/C K : 0-999° C	KC2	•	•	•	•	•
	T/C K : 0-1300° C (4 digit display)	KC3	•	•	•	•	•
	T/C T : 0-400° C	TC1	•	•	•	•	•
	T/C L : 0-500° C	LC1	•	•	•	•	•
	T/C S : 0-1600° C (4 digit display)	SC1	•	•	•	•	•
	T/C R : 0-1600° C (4 digit display)	RC1	•	•	•	•	•
	T/C N : 0-1300° C (4 digit display)	NC1	•	•	•	•	•
	PT100 : 0-100° C	PC1	•	•	•	•	•
	PT100 : 0-200° C	PC2	•	•	•	•	•
	PT100 : 0-400° C	PC3	•	•	•	•	•
	PT100 : -40-60° C	PC4	•	•	•	•	•
	PT100 : 0-600° C	PC6	•	•	•	•	•

(Note 4)

TABLE III (continued)		DC Selection	Availability				
			10N	10D	11A	11T	12N
Input Type	T/C J : 32-572° F	JF1	•	•	•	•	•
	T/C J : 32-752° F	JF2	•	•	•	•	•
	T/C J : 32-999° F	JF3	•	•	•	•	•
	T/C K : 32-999° F	KF1	•	•	•	•	•
	T/C K : 32-2372° F (4 digit display)	KF2	•	•	•	•	•
	T/C T : 32-752° F	TF1	•	•	•	•	•
	T/C L : 32-932° F	LF1	•	•	•	•	•
	T/C S : 32-2912° F (4 digit display)	SF1	•	•	•	•	•
	T/C R : 32-2912° F (4 digit display)	RF1	•	•	•	•	•
	T/C N : 32-2912° F (4 digit display)	NF1	•	•	•	•	•
	PT100 : 32-212° F	PF1	•	•	•	•	•
	PT100 : 32-392° F	PF2	•	•	•	•	•
	PT100 : 32-752° F	PF3	•	•	•	•	•
	PT100: -40-140° F (Note 4)	PF4	•	•	•	•	•
	PT100 : 32-1112° F (4 digit display)	PF6	•	•	•	•	•
	Linear 10-50 mV / 4-20 mA (Note 2)	LN1	•	•	•	•	•
Linear 0-50mV / 0-20 mA (Note 2)	LN2	•	•	•	•	•	

TABLE IV

Alarm Type						
None		0 0	•	•	•	•
PV High		P H			•	
PV Low		P L			•	
Dev High		D H			•	
Dev Low		D L			•	
Band		B A			•	

TABLE V

Custom Configuration						
None		0 0	•	•	•	•
PID Algorithm (4 digit display) (Note 3)		0 1	•	•	•	•
Special: Consult Factory		X X	•	•	•	•

TABLE VI

No Selection						
None		0	•	•	•	•

TABLE VII

Custom Model						
None		0 0 0 0	•	•	•	•
Completed Configuration Sheet Required		X X X X	•	•	•	•

Note 1: Standard is 3 digit display except as noted. 3 digit display units cannot be field configured to 4 digit display inputs.

Note 2: High & low limit range default values are 100 & 0 respectively. Contact Ft. Washington Marketing if other values needed

Note 3: PID setting can be accessed via front panel. Without this option, all UDC100 controllers are 'on/off' controllers

Note 4: Input accuracy of 0.5% span is only guaranteed by factory selection (field configuration gives 1% accuracy)

Accessories

Configurator	UDC100 PC Configuration Package : Part # 46191310-501
--------------	---