

TECHNICAL DATA SHEET

INDUSTRIAL ★ STAR ★ SERIES
for Liquid Flow Measurement

- ◆ Low Cost
- ◆ Reliable
- ◆ Accurate
- ◆ Rugged



Model Number											Technical Data			
Flowmeter Size (Inches) Size (Inches)				(Refer Note 1) Linear Flow Range (US GPM)		(Refer Note 2) Bearing Type	(Refer Note 3) Magnetic Pickup Coils	MNPT End Fitting	IND Series	Approvals	Nominal Pulses/Gallon 'K' Factor Pulses/Gallon	Nominal Max. Frequency (Hz)	Length (inches)	Working Pressure PSI
				Min.	Max.									
Model HO	1/2	X	1/4A	-.35	-3.5	-C -BP	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	15000	1000	2.45	6000
Model HO	1/2	X	3/8A	-.75	-7.5	-C -BP	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	9500	1200	2.45	6000
Model HO	1/2	X	1/2A	-1.25	-9.5	-C -BP	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	5800	1000	2.45	6000
Model HO	3/4	X	5/8A	-1.75	-16	-C -BP	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	5200	1500	2.75	6000
Model HO	3/4	X	3/4	-2.5	-29	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	2200	1000	3.25	4400
Model HO	1	X	1	-4	-60	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	816	816	3.50	3850
Model HO	1 1/4	X	1 1/4	-6	-93	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	450	670	3.88	3850
Model HO	1 1/2	X	1 1/2	-8	-130	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	215	500	4.38	3500
Model HO	2	X	2	-15	-225	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	126	500	4.75	3000
Model HO	2 1/2	X	2 1/2	-25	-400	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	80	600	6.06	1100
Model HO	3	X	3	-40	-650	-C -CB	-1M -1MX -1MX3/0	-NPT	-IND	-PED-CE -CE	45	500	7.50	1500

FLOW RANGE (Note 1) Ranges shown are standard ranges; other ranges are available. Contact Hoffer Flow Controls, Inc.

BEARING TYPE (Note 2)

C = Hard Carbon Composite sleeve bearing (standard).

BP = Shielded, self-lubricating hybrid ceramic ball bearing (optional 5/8" & below).

CB = Shielded, self-lubricating hybrid ceramic ball bearing (optional 3/4" to 3").

PICKUP COILS (Note 3)

1M = Standard magnetic pickup coil.

1MX = Magnetic pickup coil with 1" riser on meter body for mounting of enclosures and electronics.

1MX3/0 = Magnetic pickup coil with 1" riser and enclosure Class I, Groups C & D.

APPROVALS

PED-CE = PED-CE mark required for Europe requires the operating temperature and pressure be given and will be marked on the housing.

CE = CE mark required for Europe.

PERFORMANCE SPECIFICATIONS

*Linearity:	± 1.0% of reading or better.
Repeatability:	± 0.1% of reading or better.
Temperature Range:	-20°F to +450°F (Standard).
Signal Output:	10 MVRMS or greater into a 10K ohm load at minimum flow rate.

Materials of Construction:

Type 316/316L dual rated Stainless Steel (with exceptions noted below).

Rotor: 17.4 PH Stainless Steel.

Bearings:

Hard Carbon Composite (Standard).

Shielded, Self-lubricating Hybrid Ceramic Ball Bearings (Optional).

**Based on K-Factor Calibration at 70°F.*

COMPANY PROFILE

HOFFER FLOW CONTROLS, INC. has been designing and manufacturing high quality turbine flowmeters since 1968. Our ★STAR★Series should be considered when cost is a primary concern.

The ★STAR★Series is offered in eleven popular sizes that are readily available.

Simplicity

- ★ The Hoffer Turbine Flowmeter construction is simple, allowing for rugged and dependable service at low cost.

Timely Deliveries

- ★ Off-the-shelf delivery for ★STAR★Series Industrial Turbine Flowmeters. Companion electronics are also readily available with typical deliveries of 10 to 15 days.

Accuracy

- ★ Outstanding accuracy at low cost, without compromise in design. Accuracy ± 1.0% of reading or better. Repeatability ± 0.1%.

Reliability

- ★ Hoffer Flow Controls has been supplying turbine flowmeters to industry for over two decades. Our customers are repeat customers. Today our reputation is synonymous with high-quality, reliable flow systems.

In addition to the Industrial ★STAR★Series, HOFFER offers a full line of precision turbines for liquid and gas, mini-flowmeters for low-flow liquid and gas applications, profile insertion flowmeters for liquids and gases, as well as a complete line of electronic support equipment, including flow computers and linearizers. Contact the Applications Group at HOFFER for assistance.

NOTE: Spare parts are available for the ★STAR★Series to facilitate field repairs. The factory does not provide repair service on this series since it is generally more economical to replace the flowmeter.

Some industrial process applications for the ★STAR★Series are listed below *but are not limited to:*

- | | |
|----------------------------------|-------------------|
| ◆ Water Flood Secondary Recovery | ◆ Gasoline |
| ◆ Fuel Metering Systems | ◆ Well Water |
| ◆ Chemicals | ◆ Glycerine |
| ◆ Petroleum Products | ◆ Ethylene Glycol |
| ◆ Crude Oil | ◆ Alcohol |
| | ◆ Benzene |

H **HOFFER FLOW CONTROLS, INC.**
107 Kitty Hawk Lane, P. O. Box 2145, Elizabeth City, NC 27906-2145
800-628-4584 252-331-1997 FAX 252-331-2886
www.hofferflow.com
email: info@hofferflow.com

The specifications contained herein are subject to change without notice and any user of said specifications should verify from the manufacturer that the specifications are currently in effect. Otherwise, the manufacturer assumes no responsibility for the use of specifications which may have been changed and are no longer in effect.

The quality system covering the design, manufacture and testing of our products is certified to International Standard ISO 9001. Registered Company



ISO9001